

**DESCRIPTION**

Induscoat® Epsealer is a two component, high performance, clear and fast drying sealer suitable for overcoating after extended period of weathering. It also has high temperature resistance making it suitable for a wide range of applications.

**CHARACTERISTICS**

- Fast drying
- Excellent temperature resistance upto 120 °C
- For use at Newbuilding, Maintenance & Repair or On Board Maintenance.

**TECHNICAL DATA**

Type	Two-component transparent polyamide cured epoxy sealer coating
Working Time	8 hours at 30-35°C
Touch dry at 30°C(min.)	1 hour
Hard dry at 30°C(min.)	7 hours
Over coating interval	Min 4 hrs
Mixing Ratio	3:1 by volume
Volume Solids	40% ± 2% (ASTM D 2697-03)
Typical DFT	30-50 µm
Pot life at 30°C for two component paints	8-9 hrs
Theoretical covering capacity in	8 m <sup>2</sup> /liter at 50 µm
Finish	semi-glossy
Shelf Life	12 months when stored in a cool & dry place
Pack Size	20 liters. Bulk packing also available on request
Temperature Resistance	120°C

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience.

As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of willful misconduct or gross negligence on our part.

This technical data sheet supersedes all previous editions relevant to this product.

