

DESCRIPTION

Induscoat Acid & Heat Resistant Bituminous Paint (black), confirming to type I of IS 158, is a single-pack, air-drying bitumen-based coating. This self-priming solution protects steel, concrete, & cement surfaces, offering resistance to acid, alkali, & heat. With its unpigmented formulation, it ensures reliable & long-lasting surface protection.

CHARACTERISTICS

- Low moisture permeability, superior water repellence
- Excellent anti-corrosion performance
- Resistant to weathering, oxidation, mild acids, and alkali solutions
- Versatile application on steel, concrete, and more
- Easy application by brush, roller, or spray
- Suitable for surfaces in contact with fresh or salt water

TECHNICAL DATA

Type	Bitumen based paint, matte
Drying (to touch)	2 hours at 30°C
Drying (to handle)	8 hours at 30°C
Drying (to recoat)	8 hours (min) at 30°C
Volume Solids	55 % ± 2%
Typical DFT	40-60 µm in single coat
Theoretical Coverage	13.8 m ² /liter at 40 µm
Color	Black
Shelf Life	12 months when stored in cool & dry place
Pack Size	20 litres. Bulk packing also available on request

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience.

As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of willful misconduct or gross negligence on our part.

This technical data sheet supersedes all previous editions relevant to this product.

