

DESCRIPTION

Induscoat® high gloss enamel is a single pack, air drying, high gloss alkyd finishing paint. It can be used both for exterior and interior surfaces. It is a solvent based paint and can be applied on various surfaces like MS, wood, suitably finished masonry. Conforms to IS 2932.

CHARACTERSTICS

- Multipurpose glossy enamel for interior and exterior use
- Easy application by brush with excellent flow
- Good weather resistance
- Excellent colour retention
- Meets the requirement of IS:2932

TECHNICAL DATA

Finish	Smooth and glossy
Drying time	Surface : 3-4 hours Hard Dry : Overnight
Volume solids	~40%
Recommended DFT	20-25 microns
Theoretical Coverage	~20 sqmt @ 20 microns
Capacity	
Pack size	4, 20 litres, 200 litres
Shelf Life	12 months when stored in cool & dry place
Flash Point	> 35°C
Color	as per specification

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience.

As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of willful misconduct or gross negligence on our part.

This technical data sheet supersedes all previous editions relevant to this product.

